




# THETA INLAY

# **Technical Specifications**

- RF protocol EPC global Class 1 Gen 2
- Frequency 860-960 MHz (Global)
- IC type (chip)<sup>1</sup> Alien Higgs 3
- Chip memory 96 bits EPC; 64 bits serialized TID; 512 bits user memory
- Read range fixed<sup>2</sup> Up to 29.53 ft (9 m)
- Read range handheld<sup>2</sup> Up to 16.40 ft (5 m)
- Polarization Linear
- Radiation pattern off metal

Off metal-Horizontal / Vertical



### **Key Features**

- + Flexible and embeddable
- + 230°C: withstand high temperatures
- + 9 m read range: read from a distance
- + Cost effective: for high volume
- + IP68 rating: waterproof

## **Applications**

- Plastics injection molding processes
- Returnable transport items
- Automotive components
- Portable power equipment and cables


## **Environmental Specifications**

#### **Temperatures**



- Operational -40°C to +100°C
- Survival -40°C to +230°C (24 hours)
- IP rating IP68
- Compression strength 142 psi (980 kPa)
- Shock 3ft (1 m) to concrete/granite
- Vibration MIL-STD-810G
- Warranty 1 year

<sup>2</sup> Off metal






 $<sup>\</sup>frac{1}{2}$  The chip data retention is up to 50 years, based on chip operating under general environment conditions.

## **Physical Specifications**

- Material FPC
- Format Dry inlay
- **Dimensions (in)**<sup>1</sup> 2.80 x 0.43 x 0.005
- **Dimensions (mm)**<sup>1</sup> 71 x 11 x 0.13
- Weight 0.20 g



#### **Mounting Systems**

· Injection molding, Embedded

#### **Installation Instructions**

Designed to work with a wide range of thermoplastic resins and to be compatible with a large number of injection molding processes.

# **Industry Compliance**

















# **Order Information**

Theta Inlay: X7101-GL100-H3

#### **Customization Options**

xerafy.com

Encoding	
----------	--

**ATEX Certified Version** 

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet...

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.

> sales@xerafy.com Version No: 23 08 19

<sup>&</sup>lt;sup>1</sup> Tolerance: +/- 0.02; +/- 0.50