# XEBUL



# METAL SKIN TITANIUM 25 LASSO

# **Technical Specifications**

- **RF protocol** EPC global Class 1 Gen 2
- Frequency 902-928 MHz (US); 865-868 MHz (EU)
- IC type (chip)<sup>1</sup> NXP UCODE 8
- Chip memory<sup>2</sup> 128 bits EPC; 96 bits TID
- Read range fixed<sup>3</sup> Up to 26.25 ft (8 m) on metal
- Polarization Linear

#### **Key Features**

- + Lasso design: fits slim asset
- + 8m on metal: read from long distance
- + **Printable:** human and computerreadable
- + IP68 rating: waterproof

### **Applications**

- Jewelry management
- High-value item tracking
- Inventory management

## **Environmental Specifications**

#### Temperatures

Operational -40°C to +85°C
Survival -40°C to +85°C

- IP rating IP68
- Storage Humidity 50±15%RH
- **Printer compatibility** SATO CL4NX, Zebra ZT410 Silverline, Postek TX3r, etc.
- Vibration MIL-STD-810G
- Warranty l year

<sup>1</sup> The chip data retention is up to 50 years, based on chip operating under general environment conditions.

<sup>2</sup> EPC can be re-programmed or permanently locked, can not be password protected. TID is locked and unique at the point of manufacturing. <sup>3</sup> Actual read range may vary based upon use case and antenna power.

xerafy.com

sales@xerafy.com





## **Physical Specifications**

- Material White thermal transfer face stock
- Dimensions (in)<sup>1</sup> 2.68 x 0.51 x 0.04
- Dimensions (mm)<sup>1</sup> 68 x 13 x 1
- Packaging 2500pcs/roll
- Weight (roll) 4.28 lbs (1.94 kg)

#### **Mounting Systems**

· Adhesive, hanging

#### Installation Instructions

1. Clean the surface using Isopropyl alcohol, alcohol pad or equivalent solvent to ensure surface is free from dirt, dust, oil and misc, debris that may affect adhesion.

2. Handle the label by edges, peel release liner from back ensuring not to touch the adhesive.

3. Place the label in desired tagging location and firmly apply even pressure to the label for 5 seconds.

4.Do not disturb the newly mounted label for at least 15 minutes to ensure proper adhesive seating.

<sup>1</sup> Tolerance: +/- 0.02; +/- 0.50 <sup>2</sup> Tolerance: H=0.04(+/- 0.004); H=1(+/- 0.100)

### **Industry Compliance**









## **Order Information**

METAL SKIN Titanium 25 Lasso US: X6813-US011-U8 METAL SKIN Titanium 25 Lasso EU: X6813-EU011-U8

#### **Customization Options**

Encoding

Printing

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet..

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.

xerafy.com

sales@xerafy.com



13.00 mm 3.00 mm 3.00 mm

68.00 mm