



DUALBAND

Technical Specifications

- **HF protocol** ISO 15693
- **Frequency** 13.56 MHz (HF)
- **IC type** (HF chip)¹ ICODE SLIX
- **Chip memory** (HF) 64 bits UID, 896 bits user memory
- **Read range fixed**² Up to 0.16 ft (5 cm)
- **Read range handheld**² Up to 0.10 ft (3 cm)
- **RF protocol** EPC Class1 Gen2, ISO18000-6C
- **Frequency** 902-928 MHz (US); 865-868 MHz (EU)
- **IC type** (chip)¹ NXP UCODE 8
- **Chip memory** (UHF) 128 bits EPC, 96 bits TID
- **Read range fixed**³ Up to 9.84 ft (3 m)
- **Read range handheld**³ Up to 6.56 ft (2 m)
- **Polarization** Linear



Applications

- **Industrial & chemical hose, pipes**

Environmental Specifications

Temperatures⁴



- Operational -40°C to +85°C
- Survival -40°C to +125°C

- **IP rating** IP68
- **Shock** 3ft (1 m) to concrete/granite
- **Vibration** MIL-STD-810G
- **Warranty** 1 year

¹ The chip data retention is up to 50 years, based on chip operating under general environment conditions.

² HF frequency.

³ UHF frequency, on metal.

⁴ The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on chemical resistance.

Physical Specifications

- **Material** PC/PBT alloy, glue
- **Dimensions (in)**¹ 1.50 x 0.75
- **Dimensions (mm)**¹ 38.10 x 19.05
- **Thickness (in)**¹ 0.25
- **Thickness (mm)**¹ 6.35
- **Color** Yellow
- **Weight** 0.17 oz (4.90 g)

¹ Tolerance: +/- 0.004; +/- 0.100

Mounting Systems

- Metal band (Pass-through Slot 5/8")

Industry Compliance



Order Information

DUALBAND US: X3819-US100-U8

DUALBAND EU: X3819-EU100-U8

Customization Options

Encoding

ATEX Certified Version

Custom Logo

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet..

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.