



# **DATABAND2**

### **Technical Specifications**

- **HF protocol** ISO 15693
- Frequency 13.56 MHz (HF)
- IC type (HF chip) ICODE SLIX
- Chip memory (HF) 64 bits UID, 896 bits user memory
- Read range fixed<sup>2</sup> Up to 0.16 ft (5 cm)
- Read range handheld<sup>2</sup> Up to 0.10 ft (3 cm)
- RF protocol EPC Class1 Gen2, ISO18000-63
- Frequency 902-928 MHz (US); 865-868 MHz (EU)
- IC type (chip)<sup>1</sup> NXP UCODE 8
- Chip memory (UHF) 128 bits EPC, 96 bits TID
- Read range fixed Up to 9.84 ft (3 m)
- Read range handheld<sup>3</sup> Up to 6.56 ft(2 m)
- Polarization Linear



#### **Applications**

• Industrial & chemical hose, pipes

### **Environmental Specifications**

#### Temperatures<sup>4</sup>



- Operational -40°C to +85°C
- Survival -40°C to +125°C

- IP rating IP68
- Shock 3ft (1 m) to concrete/granite
- Vibration MIL-STD-810G
- Warranty 1 year

<sup>3</sup>UHF frequency, on metal.

<sup>4</sup> The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on chemical resistance.



The chip data retention is up to 50 years, based on chip operating under general environment conditions

HF frequency



### **Physical Specifications**

- Material PC/PBT alloy, glue
- **Dimensions (in)** 1.50 x 0.75
- **Dimensions (mm)** <sup>1</sup> 38.10 x 19.05
- Thickness (in) 1 0.25
- Thickness (mm)<sup>1</sup> 6.35
- Color Yellow
- Weight 0.17 oz (4.90 g)

#### **Mounting Systems**

Metal band (Pass-through Slot 5/8")

### **Industry Compliance**

















## **Order Information**

**DATABAND2 US: X3819-US100-U8** 

**DATABAND2 EU: X3819-EU100-U8** 

#### **Customization Options**

Encoding

ATEX Certified Version

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet..

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.

xerafy.com sales@xerafy.com Version No: 25 10 20



<sup>1</sup> Tolerance: +/- 0.004; +/- 0.100