



TACKTAG2

Technical Specifications

- RF protocol EPC global Class 1 Gen 2, ISO 18000-63
- Frequency 902-928 MHz (US); 865-868 MHz (EU)
- IC type (chip) NXP UCODE 9
- Chip memory 96 bits EPC; 96 bits TID
- Read rangehandheld² Up to 7 ft (2.13 m)
- Polarization Linear



Applications

- Industrial equipment
- Tools & machinery

Environmental Specifications

Temperatures



- Operational -40°C to +150°C
- Survival -40°C to +150°C

- IP rating IP68
- Shock 3 ft (1 m) to concrete/granite
- Vibration MIL-STD-810G
- Warranty 1 year

Version No: 25 11 10

³ On Metal.

The chemical resistance is based on the concentration of solutions and application environment. Please contact Xerafy for further details on chemical resistance.



xerafy.com

 $[\]frac{1}{2}$ The chip data retention is up to 50 years, based on chip operating under general environment conditions.



Physical Specifications

- Material Stainless steel, PCB
- **Dimensions (in)**¹ 0.96 x 0.59
- Dimensions (mm)¹ 24.38 x 14.99
- Thickness (in) 1 0.23
- Thickness (mm)¹ 5.84
- Weight 0.28 oz (8.50 g)

Mounting Systems

- · Welding
- · Industrial adhesive

Industry Compliance

















Order Information

TACKTAG2 US: X2415-US100-U9

TACKTAG2 EU: X2415-EU100-U9

Customization Options

Encoding

ATEX Certified Version

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet..

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.

Version No: 25 11 10

¹ Tolerance: +/- 0.004; +/- 0.100